Data Sheet

HUBER+SUHNER

Coaxial Panel Connector
22_SHV-50-0-6/133_N

Description

Straight bulkhead receptacle jack

Interface standards
IEC 60498_MIL-STD-348A/314



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	0.3 GHz

Mechanical Data

Chassis torque	2 Nm
Number of matings	500
Weight	0.0111 kg

Environmental Data

Operating temperature	-55 °C to 100 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PS (Polystyrene)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00011058
Catalogue drawing	DCA-00010449
Mounting hole	DOU-00008762

Ordering Information

Single package	22_SHV-50-0-6/133_NE

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000188667 P / PDO F / date of publication: 07.04.2020 17:47:31 / uncontrolled copy