Data Sheet

HUBER+SUHNER

RF Attenuator
6910.02.A

Description

Standard Attenuator, Low Power



Product Configuration

Connector (side 1 / side 2)	BNC plug (male) / BNC jack (female)
Interface Standards	IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Nominal impedance	75 Ω			
Nominal attenuation	10 dB			
Frequency range	DC to 1 GHz			
Frequency sub range (GHz)	DC to 0.25	0.25 to 0.4	0.4 to 0.7	0.7 to 1
Attenuation deviation (±dB)	0.3	0.3	0.3	0.8
VSWR max.	1.1	1.15	1.22	1.22
Power rating	0.75 Watt average power up to 30 ˚C ambient temperature, linearly derated to 0 Watt at 130 ˚C ambient temperature. 500 Watt peak power, 5 µs pulse, 0.05 % duty cycle			

Mechanical Data

Weight	0.025 kg

Environmental Data

Operating temperature	-55 °C to 130 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Part (side 1)	**Material**	**Surface Plating**
Centre contact	Brass	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Piece Part (side2)	**Material**	**Surface Plating**
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DCA-00005012

Ordering Information

Single packaging	6910.02.A

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000227092 U / PDO N / date of publication: 28.03.2020 00:30:38 / uncontrolled copy