Data Sheet

HUBER+SUHNER

RF Attenuator
6906.02.A

Description

Standard Attenuator, Low Power



Product Configuration

Connector (side 1 / side 2)	BNC plug (male) / BNC jack (female)
Interface Standards	IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Nominal impedance	75 Ω		
Nominal attenuation	6 dB		
Frequency range	DC to 1 GHz		
Frequency sub range (GHz)	DC to 0.5	0.5 to 0.7	0.7 to 1
Attenuation deviation (±dB)	0.3	0.3	0.8
VSWR	≤ 1.08 + 0.12 * f		
VSWR max.	1.1		
Power rating	1 Watt average power up to 30 ˚C ambient temperature, linearly derated to 0 Watt at 130 ˚C ambient temperature. 500 Watt peak power, 5 µs pulse, 0.05 % duty cycle		

Mechanical Data

Weight	0.025 kg

Environmental Data

Operating temperature	-55 °C to 130 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Part (side 1)	**Material**	**Surface Plating**
Centre contact	Brass	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Piece Part (side2)	**Material**	**Surface Plating**
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DCA-00005012

Ordering Information

Single packaging	6906.02.A

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.