Data Sheet

HUBER+SUHNER

Coaxial Cable Connector
24_QLA-01-2-1/112_N

Description

Straight bulkhead cable feed through

Interface standards
NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	1.4 GHz

Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0056 kg

Environmental Data

Operating temperature	-55 °C to 150 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Gold Plating (Nickel underplated)
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	Nickel Plating
Washer	Brass	Nickel Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Catalogue drawing	DCA-00009112
Assembly instruction	DOC-0000179088
Mounting hole	DOU-00009113

Ordering Information

Single package	24_QLA-01-2-1/112_NE

Additional Information

Suitable cables	RG_316_/U, RG_188_A/U, RG_174_/U

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000186783 W / PDO D / date of publication: 17.02.2021 17:27:48 / uncontrolled copy