

Coaxial Cable Connector
25_BNC-50-4-17/122_N

Description

Straight panel cable jack, flange mount

Interface standards
EN4652-112-B50



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
Frequency range	DC to 4 GHz
Return loss	23.1 dB

Mechanical Data

Centre contact	plugged
Outer contact	clamped
Weight	0.026 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Nickel Plating
Body	Brass	Nickel Plating
Other body part	Stainless Steel	Passivated (Plating)
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00226461
Assembly instruction	DOC-0000404480
Mounting hole	DPA-00005504

Ordering Information

Single package	25_BNC-50-4-17/122_NE
----------------	-----------------------

Additional Information

Suitable cables	KX_EN4604-010
-----------------	---------------