

Coaxial Cable Connector 25_N-50-6-9/122_N

Description

Straight panel cable jack, flange mount

Interface standards
EN4652-312-A50



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz
Frequency range	DC to 6 GHz
Return loss	23.1 dB

Mechanical Data

Centre contact	plugged
Outer contact	clamped
Weight	0.052 kg

Environmental Data

Operating temperature	-60 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Nickel Plating
Body	Brass	Nickel Plating
Other body part	Stainless Steel	Passivated (Plating)
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00223533
Assembly instruction	DOC-0000398349
Mounting hole	DOU-00008795

Ordering Information

Single package	25_N-50-6-9/122_NE
----------------	--------------------

Additional Information

Suitable cables	KW_EN4604-009
-----------------	---------------