

Coaxial Cable Connector 24_QN-50-4-1/133_N

Description

Straight bulkhead cable feed through

Interface standards

QN QLF compliant

Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	11 GHz		
Frequency range	DC to 2 GHz	2 to 4 GHz	4 to 6 GHz
Return loss	33 dB	25 dB	22 dB

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0207 kg

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00048199
Assembly instruction	DOC-0000201817
Mounting hole	DOU-00008737

Ordering Information

Bulk 100 pcs package	24_QN-50-4-1/133_NH
----------------------	---------------------

Additional Information

Suitable cables	SPUMA_240-FR-01, Spuma_240-RS-FR, SPUMA_240, LMR-240
-----------------	--