
PRODUCT DATA SHEET



A) SPECIFICATIONS

1 *Stainless steel bow*
Hooking on 40x40mm angular
2 *Self-locking pressure screw M6*
3 *Stainless steel sliding pressure plate.*
4 *SEP black P.A. fiberglass saddles*

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

IST026

CODE	ARTICLE	Nº CABLES	L	ø CABLES	BOX	WEIGHT
60 1511 0814	OX A4 / 2 x 12	2	12	6 - 12	100	62
60 1511 0816	OX A4 / 2 x 22	2	22	12 - 22	100	104
60 1511 0818	OX A4 / 2 x 34	2	34	22 - 34	100	170

RI	DATE	DR	DATE	AP
02				
01				
00	31/08/16	G.S.	31/08/16	A.V.
	1ST EMISSION			

Description:

Stainless cable clamps type OX A4
For 2 coaxial cables, complete with 4 saddles.
For articles see schedule.

FIMO® Setting Installation Standards

RoHS Compliant · RoHS 2002/95/EC

Use:

Fastening of 2 coaxial cables.
Hooking on 40x40mm angular

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.