


# PRODUCT DATA SHEET



## A) SPECIFICATIONS

- 1 Tinned Brass contact bar
- 2 Butyl strip
- 3 Tin-plated copper mesh
- 4 Protecting and sealing self-agglomerating silicone tape. Color black on reel
- 5 Rigid 7x1.70= 16mm² copper cable, black P.E. insulation
- 6 Cable lug Ø8: Tinned copper

## B) RESISTANCE TEST

### Lightning test:

Peak Current 100 kA (10/350  $\mu$ s)

Charge 50C

Protection Level III-IV in accordance with IEC 61312-1 Standard

### Water Tightness:

IP 68 (FIMO Test in accordance with IEC60529)

### Corrosion Test:

Salt Spray test in accordance with ISO 9227 Standard

**Contact Resistance:**  $\leq 1$  mOhm

**Operating Temperature:** -50°C +80 °C

## C) DELIVERY MODALITIES

Packing in boxes ok 10 kits

Label indicanting:

product code, article, production, batch

FIMO logo and picture

(customer code on request)

## D) MOUNTING INSTRUCTION

UEK IST 024 REV 0

|         |                   |
|---------|-------------------|
| code    | <b>6115050002</b> |
| article | UEK 2 M           |

|                                                                                       |                                                                                       |
|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |
| 10                                                                                    | 0.0743kg                                                                              |

| RI                                                                                 | DATE       | DR   | DATE       | AP                                                                                  | <i>Description:</i><br><br><b>UEK 2 M=monoblock earthing Kit<br/>for Cables d. 12-30</b>                                                                                                   |
|------------------------------------------------------------------------------------|------------|------|------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 02                                                                                 |            |      |            |                                                                                     |                                                                                                                                                                                            |
| 01                                                                                 |            |      |            |                                                                                     |                                                                                                                                                                                            |
| 00                                                                                 | 17/06/2014 | E.B. | 17/06/2014 | A.V.                                                                                |                                                                                                                                                                                            |
| 1 <sup>st</sup> EMISSION                                                           |            |      |            |                                                                                     |                                                                                                                                                                                            |
|  |            |      |            |  | <i>Use:</i> Earthing of coaxial cables and elliptic or rectangular waveguides<br>Coaxial Cable : 1/2"S - 3/8" - 1/2" - 5/8" - 7/8"S - 7/8"<br>Elliptic guide : 105 - 127 - 130 - 150 - 190 |