
PRODUCT DATA SHEET



A) SPECIFICATIONS

1 *Stainless steel AISI304 bow*
Hooking on flat 3-25 and round ø 8-25.
2 *Self-locking pressure screw M6 or M8 AISI304*
3 *Stainless steel AISI304 sliding pressure plate.*
4 *SAS black P.A.fiberglass saddles*

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to IEC 60068-2-6
Corrosion test: UNI EN ISO 9227
Operating temperature: -30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

IST026

CODE	ARTICLE	ø D	L	H	BOX	WEIGHT
61 1556 0206	sRF M/ 2x6	5 - 6	12	33	50	58
61 1556 0207	sRF M/ 2x7	6 - 7	12	33	50	58
61 1556 0208	sRF M/ 2x8	7 - 8	12	33	50	58
61 1556 0209	sRF M/ 2x9	8 - 9	12	33	50	58
61 1556 0291	sRF M/ 2x9 M	9 - 10	12	33	50	58
61 1556 0210	sRF M/ 2x10	10 - 11	12	33	50	56
61 1556 0211	sRF M/ 2x11	10 - 11	22	63	50	106
61 1556 2012	sRF M/ 2x12	11 - 12	22	63	50	106
61 1556 0213	sRF M/ 2x13	12 - 13	22	63	50	106
61 1556 0214	sRF M/ 2x1/2"S (14)	13 - 14	22	63	50	106
61 1556 0238	sRF M/ 2x3/8" (16)	15 - 16	22	63	50	102
61 1556 0212	sRF M/ 2x1/2" (17)	16 - 17	22	63	50	98
61 1556 0258	sRF M/ 2x5/8" (23)	21 - 23	34	87	50	171
61 1556 0227	sRF M/ 2x7/8"S (27)	26 - 27	34	87	50	166
61 1556 0278	sRF M/ 2x7/8" (28)	27 - 28	34	87	50	166
61 1556 2178	sRF M/ 2x7/8"M (30)	29 - 30	34	87	50	165
61 1556 2118	sRF M/ 2x1.1/8" (38)	36 - 38	46	111	50	238
61 1556 2114	sRF M/ 2x1.1/4" (40)	39 - 40	46	111	50	238
61 1556 2148	sRF M/ 2x1.5/8"S (49)	48 - 49	58	137	25	213
61 1556 2158	sRF M/ 2x1.5/8" (52)	50 - 52	58	137	25	211
61 1556 2214	sRF M/ 2x2.1/4" (60)	59 - 60	70	161	25	352
61 1556 0262	sRF M/ 2x62	60 - 62	70	161	25	337

RI	DATE	DR	DATE	AP
02				
01				
00	06/10/15	G.S.	06/10/15	A.V.
	1ST EMISSION			


Description:

Stainless cable clamps type sRF M
For 2 coaxial cables, complete with 4 calibrated saddles.
For articles see schedule.

FIMO®
Setting Installation Standards

RoHS compliant · RoHS 2002/95/EC

Use: *Fixing of 2 cables on flat 3-25 and round ø 8-25.*



FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.