# Data Sheet

HUBER+SUHNER

## Coaxial Panel Connector
## 23_BNC-50-0-12/133_N

## Description

Straight panel receptacle jack, flange mount



Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120

## Technical Data

### Electrical Data

| | |
|---|---|
| Impedance | 50 Ω |
| Interface frequency max. | 4 GHz |

### Mechanical Data

| | |
|---|---|
| Number of matings | 500 |
| Weight | 0.0105 kg |

### Environmental Data

| | |
|---|---|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

### Material Data

| Piece Parts | Material | Surface Plating |
|---|---|---|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

## Related Documents

| | |
|---|---|
| Outline drawing | DOU-00011017 |
| Catalogue drawing | DCA-00011018 |
| Mounting hole | DOU-00009051 |

## Ordering Information

| | |
|---|---|
| Single package | 23_BNC-50-0-12/133_NE |



Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.