Data Sheet

HUBER+SUHNER

Coaxial Cable Connector
11_BNC-50-7-16/122_U

Description

Straight cable plug

Interface standards
ABS2087.F02

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0431 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (without Nickel underplating)
Outer contact	Brass	Nickel Plating
Body	Brass	Nickel Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	Nickel Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Brass	Nickel Plating

Related Documents

Outline drawing	DOU-00102195

Ordering Information

Single package	11_BNC-50-7-16/122_UE

Additional Information

Remarks

Suitable cables: WD_EN4604--008, WN_EN4604-007

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.