

## Coaxial Cable Connector 16\_QLA-01-2-4/122\_N

### Description

Right angle cable plug

Interface standards

NIM-CAMAC-Standard CD/N549



### Technical Data

#### Electrical Data

|                          |         |
|--------------------------|---------|
| Impedance                | 50 Ω    |
| Interface frequency max. | 1.4 GHz |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | soldered  |
| Outer contact  | crimped   |
| Weight         | 0.0048 kg |

#### Environmental Data

|                                                      |                  |
|------------------------------------------------------|------------------|
| Operating temperature                                | -55 °C to 150 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant        |

#### Material Data

| Piece Parts    | Material   | Surface Plating                   |
|----------------|------------|-----------------------------------|
| Centre contact | Brass      | Gold Plating (Nickel underplated) |
| Outer contact  | Brass      | Nickel Plating                    |
| Body           | Brass      | Nickel Plating                    |
| Insulator      | PFA / PTFE |                                   |
| Crimp ferrule  | Copper     | SUCOPLATE (R) Plating             |

### Related Documents

|                      |                |
|----------------------|----------------|
| Catalogue drawing    | DOU-00006830   |
| Assembly instruction | DOC-0000179948 |

### Ordering Information

|                |                      |
|----------------|----------------------|
| Single package | 16_QLA-01-2-4/122_NE |
|----------------|----------------------|

### Additional Information

|                 |                                        |
|-----------------|----------------------------------------|
| Suitable cables | K_02252_D, ENVIROFLEX_316_D, G_02232_D |
|-----------------|----------------------------------------|