Data Sheet

EMP Protector
3400.17.0385

Description

Quarter-wave stub technology

Benefits

The protector can also be installed reversely

Compliant to IEC 61643-21

Product Configuration

Main path connectors	Port 1: unprotected, N jack (female) - Port 2: protected, N jack (female)
Mounting and grounding	MH25 (bulkhead mounting), M8 (screw), brk (bracket)

Technical Data

Electrical Data

Impedance	50 Ω
Frequency range	950 - 1450 MHz
Return loss	≥ 20 dB
Insertion loss	≤ 0.1 dB
RF CW power	≤ 500 W
PIM 3rd order	not specified
Surge current handling capability	50 multiple kA (test pulse 8/20 µs)
Residual pulse energy	5 µJ typically (test pulse 4 kV 1.2/50 µs / 2 kA 8/20 µs) main path - protected side

Mechanical Data

Number of matings	500
Weight	334 g

Environmental Data

Operating temperature	-40 °C to +85 °C
Waterproof degree	IP65 (according to IEC 60529, data refer to the coupled state)
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Housing	Brass	SUCOPLATE (R) Plating
Port 1 center contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Port 2 center contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)

Related Documents

Outline drawing	DOU-00003523
Mounting instruction	DOC-0000176104

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000176670 Y / PDO G / date of publication: 16.11.2020 17:55:17 / uncontrolled copy