Data Sheet

HUBER+SUHNER

Coaxial Cable Connector
21_SK-50-2-61/199_N

Description

Straight cable jack

Interface standards
MIL-STD-348A/323

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	40 GHz
Frequency range	DC to 40 GHz
Return loss	21 dB

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.00426 kg

Environmental Data

Operating temperature	-55 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	PPE (Polyphenylene ether, PPO)	

Related Documents

Outline drawing	DOU-00150809
Catalogue drawing	DCA-00221092
Assembly instruction	DOC-0000326138

Ordering Information

Single package	21_SK-50-2-61/199_NE

Additional Information

Suitable cables	MULTIFLEX_86

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.