Data Sheet

HUBER+SUHNER

RF TERMINATION
Type 65_MMCX-50-0-31

Description

Standard Termination, Low Power



Product Configuration

Connector	MMCX jack (female)
Interface standards	HUBER+SUHNER - MMCX

Technical Data

Electrical Data

Nominal Impedance	50 Ω
Frequency range	0 to 3 GHz
VSWR max.	1.22
Power rating	0.5 Watt average power up to 30 ˚C ambient temperature, linearly derated to 0 Watt at 85 ˚C ambient temperature.

Mechanical Data

Weight	0.0014 kg

Environmental Data

Operating temperature	-55 °C to 85 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00008667

Ordering Information

Single Packaging Packaging	65_MMCX-50-0-31/111_OE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000184756 AA / PDO J / date of publication: 28.03.2020 00:35:47 / uncontrolled copy