Data Sheet

HUBER+SUHNER

Coaxial Cable Connector
21_N-50-3-51/19-_N

Description

Straight cable jack

Interface standards
IEC 61169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
Frequency range	DC to GHz

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.0358 kg

Environmental Data

Operating temperature	-55 °C to 70 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel / Brass	
Insulator	Air Dielectric - Bead - PPH	

Related Documents

Catalogue drawing	DOU-00007140
Assembly instruction	DOC-0000180866

Ordering Information

Single package	21_N-50-3-51/19-_NE

Additional Information

Suitable cables	SUCOFORM_141, EZ_141_TP_M17, MULTIFLEX_141

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.