

PRODUCT DATA SHEET





A) SPECIFICATIONS

1 SEB calibrated double saddle P.P. black
2 Threaded bar - BFI M8 (SS)
3 Washers (SS)
4 Hexagonal Nuts M8 (SS)
5 Compact Clamp MIM 8/25 (SS)

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -40°C +85°C

C DELIVERY MODALITIES

Packing in boxes.
Label indicating:
product code, article, quantity, production batch, FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

on request

CODE	ARTICLE	ø D	L	h	H	BOX	WEIGHT
61 1566 0208	**UMC 2x8**	7 - 8	51	20	50	20	145
61 1566 0209	**UMC 2x9**	8 - 9	51	20	50	20	145
61 1566 0211	**UMC 2x11**	10 - 11	51	20	50	20	145
61 1566 0213	**UMC 2x13**	12 - 13	60	27	75	20	158
61 1566 0214*	**UMC 2x1/2"S***	13 - 14	60	27	75	20	158
61 1566 0212	**UMC 2x1/2" (17)**	16 - 17	60	27	75	20	158
61 1566 0258	**UMC 2x5/8" (23)**	21 - 23	84	37	75	20	199
61 1566 0278	**UMC 2x7/8" (28)**	27 - 28	84	37	75	20	199
61 1566 2114	**UMC 2x1.1/4" (40)**	39 - 40	108	54	100	20	231
61 1566 2158	**UMC 2x1.5/8" (52)**	50 - 52	133	66	100	20	240

article **UMC 2**

RI	DATE	DR	DATE	AP
02				
01				
00	31/03/16	G.S.	31/03/16	A.V.
	1ST EMISSION			

Description:

Universal cable clamps with MIM 8/25 compact clamp.
For 2 coaxial cables, complete with 2 calibrated saddles.
For articles see schedule.

FIMO® Setting Installation Standards

RoHS compliant. RoHS 2002/95/EC

Use:

Fastening of 2 coaxial cables on flat, round, angular

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.