
PRODUCT DATA SHEET



A) SPECIFICATIONS

1 *Stainless steel threaded bar BFI M8*
2 *Stainless steel flat Washer RPI 8/16*
3 *Stainless steel hexagonal nut DAI 8*
4 *SAM Single saddle P.P. U.V. resistant*

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -50°C +80°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

On request

CODE	ARTICLE	ø D	L	h	H	WEIGHT
61 1571 0411	USO/ 4x11	10 - 11	44	125	84	95
61 1571 0414	USO/ 4x1/2"S (14)	13 - 14	50	150	108	172
61 1571 0412	USO/ 4x1/2" (17)	16 - 17	50	150	108	172
61 1571 0478	USO/ 4x7/8" (28)	27 - 28	59	200	152	185
61 1571 4114	USO/ 4x1.1/4" (40)	39 - 40	70	300	216	235
61 1571 4158	USO/ 4x1.5/8" (52)	50 - 52	80	400	264	323

RI	DATE	DR	DATE	AP
02				
01				
00	06/10/15	G.S.	06/10/15	A.V.
	1ST EMISSION			

Description:

USO

Cable Clamps for flat iron with holes

FIMO® Setting Installation Standards

RoHS

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.