

Coaxial Cable Connector 11_BNC-75-4-39/133_N

Description

Straight cable plug

Interface standards

Interface compatible with IEC 61169-8



Technical Data

Electrical Data

Impedance	75 Ω			
Interface frequency max.	4 GHz			
Frequency range	DC to 1 GHz	1 to 2 GHz		2 to 3 GHz
Return loss	38 dB	31 dB		24 dB

Mechanical Data

Centre contact	crimped
Outer contact	crimped

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Bronze	SUCOPLATE (R) Plating
Body	Bronze	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00115935
Catalogue drawing	DCA-00198322
Assembly instruction	DOC-0000270231

Ordering Information

Single package	11_BNC-75-4-39/133_NE
----------------	-----------------------

Additional Information

Remarks

for HDTV applications RL values are relevant for Draka 0.8/3.7 AF cable