

## Coaxial Cable Connector 16\_MMCX-50-2-13/111\_O

### Description

Right angle cable plug

Interface standards  
SUHNER-MMCX



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 50 $\Omega$ |
| Interface frequency max. | 6 GHz       |

#### Mechanical Data

|                |          |
|----------------|----------|
| Centre contact | soldered |
| Outer contact  | soldered |

#### Environmental Data

|                                                      |                  |
|------------------------------------------------------|------------------|
| Operating temperature                                | -55 °C to 155 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant        |

#### Material Data

| Piece Parts    | Material   | Surface Plating                            |
|----------------|------------|--------------------------------------------|
| Centre contact | Brass      | Gold Plating (Nickel underplated)          |
| Outer contact  | Brass      | Gold Plating (without Nickel underplating) |
| Body           | Brass      | Gold Plating (without Nickel underplating) |
| Insulator      | PFA / PTFE |                                            |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00048327   |
| Catalogue drawing    | DCA-00091046   |
| Assembly instruction | DOC-0000214734 |

### Ordering Information

|                      |                        |
|----------------------|------------------------|
| Bulk 100 pcs package | 16_MMCX-50-2-13/111_OH |
| Single package       | 16_MMCX-50-2-13/111_OE |

### Additional Information

|                 |                                         |
|-----------------|-----------------------------------------|
| Suitable cables | SUCOFORM_86, EZ_86_TP_M17, MULTIFLEX_86 |
|-----------------|-----------------------------------------|