Data Sheet

Coaxial Cable Connector
16_MMCX-50-2-2/111_O

Description

Right angle cable plug

Interface standards
SUHNER-MMCX



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0008 kg

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Crimp ferrule	Copper	Gold Plating (without Nickel underplating)

Related Documents

Outline drawing	DOU-00007188
Catalogue drawing	DOU-00006005
Assembly instruction	DOC-0000241538

Ordering Information

Bulk 100 pcs package	16_MMCX-50-2-2/111_OH
Single package	16_MMCX-50-2-2/111_OE

Additional Information

Suitable cables	K_02252_D, ENVIROFLEX_316_D, G_02232_D

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.