# Data Sheet

HUBER+SUHNER

## Coaxial Panel Connector
## 23_SMA-50-0-272/133_N

## Description

Straight panel receptacle jack, flange mount



Interface standards
IEC 60169-15_MIL-STD-348A/310_CECC 22110

## Technical Data

### Electrical Data

| | |
|---|---|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

### Mechanical Data

| | |
|---|---|
| Number of matings | 500 |
| Weight | 0.002 kg |

### Environmental Data

| | |
|---|---|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

### Material Data

| Piece Parts | Material | Surface Plating |
|---|---|---|
| Centre contact | Copper Beryllium Alloy | SUCOPRO Plating |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

## Related Documents

| | |
|---|---|
| Outline drawing | DOU-00051629 |
| Catalogue drawing | DCA-00181395 |

## Ordering Information

| | |
|---|---|
| Bulk 100 pcs package | 23_SMA-50-0-272/133_NH |



Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000189061 L / PDO H / date of publication: 07.04.2020 18:09:09 / uncontrolled copy