Data Sheet

Coaxial Cable Connector
11_MBX-50-2-1/113_N

Description

Straight cable plug

Interface standards
HUBER+SUHNER MBX



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.003546 kg

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze / Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00162030
Catalogue drawing	DCA-00161650
Assembly instruction	DOC-0000333519

Ordering Information

Bulk 100 pcs package	11_MBX-50-2-1/113_NH
Single package	11_MBX-50-2-1/113_NE

Additional Information

Suitable cables	ENVIROFLEX_316_D, K_02252_D, G_02232_D

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.