Data Sheet

HUBER+SUHNER

Coaxial Panel Connector
23_SHV-50-0-2/133_N

Description

Straight panel receptacle jack, flange mount



Interface standards
IEC 60498_MIL-STD-348A/314

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	0.3 GHz

Mechanical Data

Number of matings	500
Weight	0.0143 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00068553
Catalogue drawing	DCA-00011171
Mounting hole	DOU-00010585

Ordering Information

Single package	23_SHV-50-0-2/133_NE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000188937 O / PDO D / date of publication: 27.03.2020 19:53:48 / uncontrolled copy