# Data Sheet

HUBER+SUHNER

## Coaxial Cable Connector
## 26_TNC-50-3-1/122_U

## Description

Right angle cable jack

Interface standards
ASNE.0461.TF01

## Technical Data

### Electrical Data

| | | |
|---|---|---|
| Impedance | 50 Ω | |
| Interface frequency max. | 11 GHz | |
| Frequency range | DC to 3 GHz | 3 to 6 GHz |
| Return loss | 24.9 dB | 15.6 dB |

### Mechanical Data

| | |
|---|---|
| Centre contact | crimped |
| Outer contact | crimped |
| Weight | 0.0612 kg |

### Environmental Data

| | |
|---|---|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

### Material Data

| Piece Parts | Material | Surface Plating |
|---|---|---|
| Centre contact | Copper Beryllium Alloy | Gold Plating (without Nickel underplating) |
| Outer contact | Brass | Nickel Plating |
| Body | Brass | Nickel Plating |
| Insulator | PFA / PTFE | |

## Related Documents

| | |
|---|---|
| Outline drawing | DOU-00126413 |

## Ordering Information

| | |
|---|---|
| Single package | 26_TNC-50-3-1 |

## Additional Information

| | |
|---|---|
| Suitable cables | RG_400_/U, ASNE0293 XF |

## Remarks



Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.