Data Sheet

HUBER+SUHNER

Coaxial Panel Connector
13_BNC-50-0-1/133_N

Description

Straight panel receptacle plug, flange mount



Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz

Mechanical Data

Number of matings	500
Weight	0.0147 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00010214
Catalogue drawing	DCA-00010216
Mounting hole	DOU-00009051

Ordering Information

Single package	13_BNC-50-0-1/133_NE

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000187431 N / PDO C / date of publication: 07.04.2020 18:07:52 / uncontrolled copy