Data Sheet

HUBER+SUHNER

Coaxial PCB Connector
82_QMA-S50-0-2/111_N

Description

Straight PCB jack

Interface Standards
QMA QLF compliant

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

Mechanical Data

Board mounting type	surface mount
Weight	0.0012 kg

Environmental Data

Operating temperature	-40 °C to 85 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00012672
Catalogue drawing	DCA-00012674
Mounting hole	DOU-00012675

Ordering Information

Bulk 100 pcs package	82_QMA-S50-0-2/111_NH

Remarks

PCB connector with stand-offs

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.