1 1/4"-A

STANDARD

Cable type : *5328 A*

Reference : *EC6-50-A*

Cable with standard UV resistant PE jacket, halogen free according to IEC 60754

CHARACTERISTICS

Construction

• Inner conductor	
Material	**smooth copper tube**
Diameter *(mm)*	**13.0**
• Dielectric	
Material	**gas-injected cellular polyethylene**
Diameter *(mm)*	**33.5**
• Outer conductor	
Material	**corrugated copper tube**
Diameter *(mm)*	**36.0**
• Outer sheath	
Material	**black polyethylene**
Thickness *(mm)*	**1.5**
Diameter *(mm)*	**39.0**

Mechanical characteristics

• Minimum bending radius	
a) single bending *(cm)*	**20**
b) 15 repeated bends *(cm)*	**35**
• Maximum pulling strength *(daN)*	**240**
• Recommended temperature range	
- Storage	**-70 to +85 °C**
- Installation	**-40 to +60 °C**
- Operation	**-55 to +85 °C**
• Max. length per hoisting grip *(m)*	**70**
• Maximum hanger spacing *(m)*	**1.4**
• Flat plate crush resistance *(kg/mm)*	**2.4**
• Bending moment *(Nm)*	**30**
• Approximate weight[4] *(kg/km)*	**803 / 889**

Electrical characteristics

• Characteristic impedance *(Ω)*	**50 ± 1**
• Nominal capacity *(pF/m)*	**76**
• Relative propagation velocity *(%)*	**88**
• Inductance *(µH/m)*	**0.189**
• DC-resistance at 20°C	
- inner conductor *(Ω/km)*	**0.95**
- outer conductor *(Ω/km)*	**0.69**
• RF peak voltage *(kV)*	**4.3**
• RF peak power *(kW)*	**184**
• Cut-off-frequency *(GHz)*	**3.7**
• Insulation resistance *(M Ω.km)*	**>> 5000**

• Attenuation[1] and power rating

Frequency *(MHz)*	Attenuation at 20°C [2] *(dB/100m)*	Mean power rating [3] *(kW)*
10	0.25	37.13
20	0.36	26.12
30	0.44	21.24
80	0.73	12.84
100	0.81	11.44
150	1.01	9.26
200	1.17	7.96
300	1.45	6.42
400	1.69	5.51
450	1.80	5.17
500	1.91	4.88
600	2.10	4.42
700	2.29	4.07
800	2.46	3.78
894	2.62	3.56
960	2.72	3.42
1000	2.79	3.34
1500	3.50	2.66
1700	3.76	2.48
1800	3.88	2.40
1880	3.98	2.34
2000	4.12	2.26
2170	4.32	2.15
2200	4.35	2.14
2300	4.47	2.08
2400	4.58	2.03
2500	4.69	1.98
2700	4.91	1.90
3000	5.22	1.78
3400	5.62	1.66
3600	5.81	1.60

[1] The attenuation can be approximated by the formula:

$$\alpha(f[MHz]) = A \cdot \sqrt{f[MHz]} + B \cdot f[MHz] \quad (dB/100m)$$

A = 0.0783
B = 0.00031

[2] Nominal values
[3] Ambient temperature = 40°C; temperature of inner conductor = 100°C; VSWR = 1.0; no solar loading
[4] Standard PE jacket / HLFR Jacket