


# RADOX® Milcat

## Databus cable for harsh environment



### Features

- CAT5 properties
- Optimised diameter for RJ45 and other connectors
- For fix and flexible applications
- Halogen free
- Complies with RoHS directives
- Robust design


### Benefits

- Designed for harsh environment
- High speed solution
- Long life time
- Light weight and easy to process

# RADOX® Milcat

## Applications

- Military communication
- Industrial automation
- Other industrial applications in harsh environment



Technical properties	
Conductor	tinned copper, flexible, EN 60228, class 5
Insulation	RADOX® PE isolation
EMC screen	aluminium tape, plastic laminated and tin-plated copper braid
Sheath	RADOX® PU, colour black
Impedance	100 Ω at 100 MHz
Voltage rating	300 V
Construction	4 × 2 × 26 AWG
Outer diameter	7.1 mm
Temperature range	-40 to +90 °C
Item no.	12585990

## Media propertis

Very good resistance against:

- oils and fuels
- water and hydrolysis
- weather and UV radiation

HUBER+SUHNER AG  
Low Frequency Division  
Tumbelenstrasse 20  
8330 Pfäffikon/Switzerland  
Phone +41 44 952 2211  
Fax +41 44 952 2670  
hubersuhner.com

HUBER+SUHNER is certified according to EN 9100,  
ISO 9001, ISO 14001, ISO/TS 16949 and IRIS.

### Waiver

Fact and figures herein are for information only and do not represent any warranty of any kind.