
PRODUCT DATA SHEET



A) SPECIFICATIONS

1 *H.D.P.E. SAB duoble saddle*
2 *Stainless steel threaded bar BFI M8*
3 *Stainless steel elastic washer REI 8*
4 *Stainless steel hexagonal nut DAI 8*
5 *Stainless steel pressure plate PRUC*

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -50°C +80°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

On request

CODE	ARTICLE	ø D	L	h	H	BOX	WEIGHT
61 1575 0809	UCL/ 8x9	8 - 9	56	150	84	20	275
61 1575 0811	UCL/ 8x11	10 - 11	56	150	84	20	275
61 1575 0813	UCL/ 8x13	12 - 13	68	200	108	20	225
61 1575 0814	UCL/ 8x1/2"S (14)	13 - 14	68	200	108	20	225
61 1575 0838	UCL/ 8x3/8" (16)	15 - 16	68	200	108	20	225
61 1575 0812	UCL/ 6x1/2" (17)	16 - 17	68	200	108	20	225
61 1575 0858	UCL/ 8x5/8" (23)	21 - 23	90	250	152	20	480
61 1575 0878	UCL/ 8x7/8" (28)	27 - 28	90	250	152	20	480

RI	DATE	DR	DATE	AP
02				
01				
00	06/10/15	G.S.	06/10/15	A.V.
	1ST EMISSION			

Description:

Cable Clamps type UCO+2 PUC 70

FIMO® Setting Installation Standards

RoHS compliant · RoHS 2002/95/EC

Use:

Fixing of 8 cables on steel wire-mesh cable trays

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.