

FullAXS assemblies

FullAXS to LC connector, single-mode bend intensive fiber



Length	Item no.	Assembly code
5 m	84137911	MRO2_FAP2_ICUD_A248T_05.0_SS
10 m	84137912	MRO2_FAP2_ICUD_A248T_10.0_SS
20 m	84137914	MRO2_FAP2_ICUD_A248T_20.0_SS
30 m	84137915	MRO2_FAP2_ICUD_A248T_30.0_SS
40 m	84137916	MRO2_FAP2_ICUD_A248T_40.0_SS
50 m	84137917	MRO2_FAP2_ICUD_A248T_50.0_SS
60 m	84137918	MRO2_FAP2_ICUD_A248T_60.0_SS
70 m	84137919	MRO2_FAP2_ICUD_A248T_70.0_SS
80 m	84137920	MRO2_FAP2_ICUD_A248T_80.0_SS
90 m	84137921	MRO2_FAP2_ICUD_A248T_90.0_SS
100 m	84137922	MRO2_FAP2_ICUD_A248T_0100_SS
125 m	84137923	MRO2_FAP2_ICUD_A248T_0125_SS
150 m	84137924	MRO2_FAP2_ICUD_A248T_0150_SS

Connector left FullAXS plug

Type	Connector	Dust cap
FAP2	FullAXS plug 	IP65 

Connector right LC connector

Type	Connector
ICUD	LC duplex 

Used cable

Glass-armoured riser cables with 2 fibers



Item no.	Cable type	Description
84118844	O2-E9A2/F(ZNG)H-G48	2-fiber, 50/125 µm low bend acc. ITU-G.657-A2, Ø 4.8 mm, jacket LSFH black