

CD-400 Duplexer

The small size of our duplexer CD-400 solves space problems in a wide variety of applications including car phones, portable and vehicular repeaters and repeater base stations. Their design and construction features include solid shield copper jacketed inter-cabling for durability, low insertion loss, small VSWR and high Isolation.

Specifications	
Model	CD-400
Freq. Range-MHz	400-480
Freq. Spacing-MHz	10
Nominal Impedance-Ω	50
VSWR	≤1.5
Insertion Loss (Tx)-dB	1.2
Insertion Loss (Rx)-dB	1.2
Continuance Input Power -W	50
Tx Noise Suppression at Rx Frequency —dB	75
Rx Noise Suppression at Tx Frequency-dB	75
Connector Type	N Female or Customized
Dimension-mm	227.5×154×32
Weight-Kg	1
Temperature Range-°C	—30~+60



Note: Please specify the TX frequency and Rx frequency when placing order.



KENBOTONG TECHNOLOGY CO., LTD.

Addr : NO.2 Chanxiu Road ,Foshan city,Guangdong China

Code: 528061

Tel: 86(757)8202-5597, 8221-9788

Fax : 86(757)8221-2072,8802-2808

Email: kbt@kenbotong.com

web: <http://www.kenbotong.com>