
PRODUCT DATA SHEET



A) SPECIFICATIONS

1 *Calibrated twin black saddles made in H.D.P.E*
2 *Stainless steel threaded bar BFI M8*
3 *Stainless steel pressure plate PSAL*
4 *Stainless steel hexagonal nut DAI 8*
5 *Stainless steel flat Washer REI 8*
6 *MCM 8 compact clamp*

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature:-30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity, production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

On request

CODE	ARTICLE	ø D	L	h	H	BOX	WEIGHT
61 1563 2012	LCC/ 2x1/2"	15 - 17	62	75	30	20	240
61 1563 2078	LCC/ 2x7/8"	27 - 29	84	75	41	20	250
61 1563 2114	LCC/ 2x1.1/4"	38 - 40	102	100	53	20	280
61 1563 2158	LCC/ 2x1.5/8"	50 - 52	119	100	64	20	310

RI	DATE	DR	DATE	AP
02				
01				
00	03/11/2015	G.S.	03/11/2015	A.V.
	1ST EMISSION			

Description:

LCC *- LCO+MCM 8 compact clamp*

- **Side Insertion of Cables**
- **Elastic Prefixing**
- **Manual Final Locking**

FIMO® Setting Installation Standards

RoHS compliant · RoHS 2002/95/EC

Use:

Fastening of 2 cables on flat, round an angular

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.