
PRODUCT DATA SHEET



A) SPECIFICATIONS

1 *Calibrated twin black saddles made in H.D.P.E*
2 *Stainless steel threaded bar BFI M8*
3 *Stainless steel pressure plate PSAL*
4 *Stainless steel hexagonal nut DAI 8*
5 *Stainless steel flat Washer REI 8*

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature:-30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity, production batch, FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

On request

CODE	ARTICLE	ø D	L	h	H	BOX	WEIGHT
61 1562 6012	LCO/ 6x1/2"	15 - 17	62	125	84	20	215
61 1562 6078	LCO/ 6x7/8"	27 - 29	84	150	117	20	245
61 1562 6114	LCO/ 6x1.1/4"	38 - 40	102	200	153	20	335
61 1562 6158	LCO/ 6x1.5/8"	50 - 52	119	250	186	20	385

RI	DATE	DR	DATE	AP
02				
01				
00	03/11/2015	G.S.	03/11/2015	A.V.
	1ST EMISSION			

Description:

LCO *- Quick-fit Fasteners for Flat with Holes*

- **Side Insertion of Cables**
- **Elastic Prefixing**
- **Manual Final Locking**

FIMO® Setting Installation Standards

RoHS Compliant. RoHS 2002/95/EC

Use:

Fastening of 6 cables on flat iron with holes

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.