Data Sheet

HUBER+SUHNER

RF TERMINATION
Type 65_TNC-75-0-1/133_N

Description

Standard Termination, Low Power



Product Configuration

Connector	TNC plug (male)
Interface standards	IEC 60169-17_MIL-STD-348A/313_CECC 22200

Technical Data

Electrical Data

Nominal Impedance	75 Ω
Frequency range	0 to 1 GHz
VSWR max.	1.1
Power rating	1 Watt average power up to 30 ˚C ambient temperature, linearly derated to 0 Watt at 130 ˚C ambient temperature. 800 Watt peak power

Mechanical Data

Weight	0.019 kg

Environmental Data

Operating temperature	-40 °C to 130 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Ordering Information

Single Packaging Packaging	65_TNC-75-0-1/133_NE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.