TEF

Cold Shrink Tube



MATERIAL	
Tube	Silicone/ EPDM rubber*
Colour	Black

*** TEF 17 C - TEF 17: Silicone**

TEF - Cold Shrink Tube

TEF cold shrink tubes are a series of open-ended tubular silicone/EPDM rubber sleeves, pre-expanded on a removable core for easy installation. After the core is removed, the tube shrinks to its original diameter guaranteeing a perfect sealing on connectors. In applications where the different cable diameter cannot be covered with the tube range, a special foam is included in the package. The strip foam is used to increase the smaller cable diameter and assure the sealing of the clod shrink tube.

Application
Sealing of feeder connections. TEF offers a timesaving and easy way to secure a waterproof protection. No tools or heating are requested for installation. The shrinking process is done by simply unwinding the removable core.

TEF - Tubolari Retraibili a Freddo

I tubolari retraibili a freddo TEF sono una serie di manicotti in silicone/EPDM aperti agli estremi, pre-espansi su un cilindro removibile per una facile installazione. Dopo che il cilindro viene rimosso, il manicotto si retrae fino alla suo diametro originale garantendo una perfetta sigillatura dei connettori. Nelle applicazioni dove la differenza dei diametri dei cavi non può essere coperta dall'escursione del manicotto, uno speciale nastro di gomma espansa è incluso nella confezione. Il nastro di gomma espansa viene usato per aumentare il diametro del cavo minore e garantire la sigillatura del tubolare retraibile a freddo.

Applicazioni:
Sigillatura di connessioni. I TEF offrono una soluzione rapida e sicura per una protezione stagna. Né utensili né riscaldamento a mezzo di fiamma sono richiesti per l'installazione. Il processo di restringimento avviene semplicemente svolgendo il cilindro removibile.

CODE	ARTICLE	COLD SHRINK TUBE FOR	FOAM STRIP	OPERATING TEMPERATURE	ø D ORIGINAL	L SHRINKED	ø d RANGE *	BOX
61 2205 0009	TEF 17 E	1/2" to antenna	Not included	-55° / + 200° C	45	160 mm	12 – 39.0	20
61 2205 0011	TEF 17 C	3/8" or 1/2" to antenna	Not included	-55° / + 200° C	45	170 mm	10.5 – 39.0	20
61 2205 0012	TEF 17	1/2" to antenna	Not included	-55° / + 200° C	45	200 mm	13.5 – 39.0	20
61 2205 0078	TEF 28	1/2" to 7/8" 5/8" to 7/8"	included	-40° / + 200° C	53	254 mm	25.0**– 46.0	20
61 2205 0158	TEF 50	1/2" to 1.1/4" or 1.5/8" 5/8" to 1.1/4" or 1.5/8"	included	-40° / + 200° C	70	330 mm	32.0** – 63.0	20

***after shrinking, without foam strip**
****for smaller diameter cables, use the included foam strip**

Copyright © Fi.Mo.Tec. S.p.A.