

Coaxial Panel Connector 23_4310-50-0-5/003_-

Description

Straight panel receptacle jack, flange mount

Interface standards
IEC 61169-54



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 12 GHz |

Mechanical Data

| | |
|-------------------|-----------|
| Number of matings | 100 |
| Weight | 0.0394 kg |

Environmental Data

| | |
|--|-----------------|
| Operating temperature | -55 °C to 90 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|--------------------------|-----------------------|
| Centre contact | Copper Beryllium / Brass | Silver Plating |
| Outer contact | Bronze | Silver Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00263954 |
| Catalogue drawing | DCA-00264946 |

Ordering Information

| | |
|----------------|-----------------------|
| Single package | 23_4310-50-0-5/003_-E |
| Tray package | 23_4310-50-0-5/003_-Y |