

Rubber Antenna for ICOM Portable Equipment in the 2 m Band

DESCRIPTION

- Sturdy, conical, flexible rubber antenna.
- Full size $\frac{1}{4}$ λ whip.
- Highest quality materials – designed for “wear and tear”.
- Delivered factory tuned and tested to ensure minimum VSWR and optimum performance.
- Especially designed for ICOM IC-F51 (150 MHz band).



SPECIFICATIONS

Electrical	
Model	GA 2/...-IC-F51
Frequency	2 m band covered by two models
Antenna Type	$\frac{1}{4}$ λ antenna for portable equipment
Max. Input Power	100 W
Polarisation	Vertical
Impedance	50 Ω
Gain	0 dB (compared to a $\frac{1}{4}$ λ portable antenna)
VSWR	< 2.0:1 when mounted directly on portable equipment
Bandwidth	≥ 20 MHz @ VSWR ≤ 2.5
Mechanical	
Connection(s)	SMA(m) special for IC-F51
Materials	Steelwire moulded in thermoplastic rubber Weather- and shockproof plastics Black-chromed brass
Colour	Black
Height	Approx. 450 mm / 17.72 in.
Weight	Approx. 0.06 kg / 0.13 lb.

ORDERING

Model	Product No.	Frequency
GA 2/l-IC-F51	140000362	144 - 164 MHz
GA 2/h-IC-F51	140000361	155 - 175 MHz

TYPICAL VSWR CURVE

