

Rubber Antenna for Portable Equipment in the 70 cm Band

DESCRIPTION

- Sturdy, conical, flexible rubber antenna.
- Full size ¼ λ whip.
- Highest quality materials – designed for “wear and tear”.
- Delivered factory tuned and tested to ensure minimum VSWR.
- Especially designed for Motorola GP 300, GP 344, GP 360 and GP 388 (450 MHz band) etc.



SPECIFICATIONS

Electrical	
Model	GA 70/...-GP 300
Frequency	70 cm band covered by three models
Antenna Type	Antenna for portable equipment
Max. Input Power	100 W
Polarisation	Vertical
Impedance	50 Ω
Gain	0 dB (compared to a ¼ λ portable antenna)
Mechanical	
Connection(s)	1/4"-32 UNEF
Materials	Steelwire moulded in thermoplastic rubber Weather- and shockproof plastics Black-chromed brass Cu-nite brass
Colour	Black
Height	Approx. 140 mm / 5.51 in. (dep. on type)
Weight	Approx. 0.03 kg / 0.07 lb.

ORDERING

Model	Product No.	Frequency
GA 70/s-GP 300	140000368	380 - 430 MHz
GA 70/l-GP 300	140000304	400 - 450 MHz
GA 70/h-GP 300	140000305	420 - 470 MHz

TYPICAL VSWR CURVE

