

Steel-Band Antenna for ICOM Portable Equipment in the
2 m Band

DESCRIPTION

- Rugged, flexible steel-band antenna whip.
- Curved sectional area to help keeping the antenna erect.
- Full-size ¼ λ whip.
- Provided with toggle joint and wing screw for easy fold-down.
- Delivered factory tuned and tested to ensure minimum VSWR and optimum performance.
- Especially designed for ICOM IC-F51 (150 MHz band).



SPECIFICATIONS

Electrical	
Model	SB 2/...-IC-F51
Frequency	2 m band covered by two models
Antenna Type	Antenna for portable equipment
Max. Input Power	200 W
Polarisation	Vertical
Impedance	50 Ω
Gain	0 dB (compared to a ¼ λ portable antenna)
VSWR	< 2.0:1 when mounted directly on portable equipment

Mechanical	
Connection(s)	SMA(m) special for IC-F51
Materials	Stainless steel band and rubber Weather- and shockproof plastics Black-chromed brass
Colour	Black
Height	Approx. 500 mm / 19.69 in.
Weight	Approx. 0.045 kg / 0.10 lb.

ORDERING

Model	Product No.	Frequency
SB 2/l-IC-F51	140000146	144 - 164 MHz
SB 2/h-IC-F51	140000147	155 - 175 MHz

TYPICAL VSWR CURVE

