Data Sheet

HUBER+SUHNER

SENCITY® Omni-S Cellular/LTE 800 Antenna
1399.19.0224

Description

Omni - directional Cellular/4G LTE 800 SISO antenna
Supports LTE 790 to 960 MHz, Cellular 1710 to 2170 and
LTE 2300, 2500, 2600 MHz frequency bands
Single hole cabinet or wall/pole mounting
For outdoor and indoor applications
Ingress protection IP66 / IP67 (IP69k)

Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	790 - 930	930 - 960	1710 - 2170	2300 - 2690
VSWR	1.8	2.5	1.9	1.6
Impedance (Ohm)	50	50	50	50
Gain (dBi)	2	2	6	4
Composite power max (W)	60	60	50	40
Ambient temperature (°C)	25	25	25	25

Ports

	Port 1
Connector	SMA, plug (male)
Cable Type	ENVIROFLEX_316_D
Cable Length (m)	1
Min. radius static (mm)	5
Min. radius dynamic (mm)	30
Polarization	vertical
DC grounded	No

Connections

	Band 1	Band 2	Band 3	Band 4
Port 1	X	X	X	X

General Data

GROUND PLANE: Antenna works on metallic as well as on non-metallic ground plane. VSWR is valid for both mounting options
GAIN VALUES: Indicated gain values are valid for non-metallic ground plane. Gain of this antenna on metallic surface is higher for 790 to 960 MHz: 4 dBi (instead of 2 dBi)

INGRESS PROTECTION:
- IP 66, IP67 AND IP 69K when mounted on cabinet's flat surface or roof
- IP 66 and IP67 when mounted on bracket with sealed cable conduit

Mechanical Data

Dimensions (mm)	33.2 x 145 (Height x Diameter)
Weight (kg)	0.3

SENCITY® Omni-S Cellular/LTE 800 Antenna
1399.19.0224

Environmental Data

Environmental conditions	indoor/outdoor
Operation temperature (°C)	-55 to 85
Storage temperature (°C)	-55 to 85
Transport temperature (°C)	-55 to 85
Flammability rating	UL 94-V0
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
Lead-free soldered	yes
WEEE 2012/19/EU	special marking needed
REACH 1907/2006/EC	compliant

TEMPERATURE RANGE: EN 60068-2-1 (2007), test Ab, -55°C, 16h and EN-60068-2-2 (2007), test Bb, +85°C, 16h
THERMAL SHOCK: IEC 60068-2-14 (2009), test Na, -55°C to +85°C, 3h, 5 cycles
SOLAR RADIATION: EN 60068-2-5, test Sa, procedure B, 1200 W/m2, 3 x 24h
RELATIVE HUMIDITY: EN 60068-2-78 (2012), test Cb, RH 95%, 21d (damp heat, steady state)
RELATIVE HUMIDITY: EN 60068-2-30 (2005), RH 97%, 6 cycles (damp heat, cyclic)
SALT SPRAY: EN 60068-2-11 (2002), test Ka, 96h
MECHANICAL VIBRATIONI / SHOCK: IEC 61373 (1999), § 9 and § 10, category 2
VANDALISM: EN 60068-2-75 (1997), IEC 62262 (2002) IK10, test Ehc
CORROSION: MIL-F-14072 E type 1 "exposed"

Material Data

Radome colour	RAL 7044 (grey)
Radome material	PC (Polycarbonate)

Related Products

9091.99.0259 Bracket kit for SENCITY® Omni-S MIMO antenna
Accessory kit 9091.99.0259 is available via H+S customizing process, no item number as extra deliverable assigned yet.

Related Documents

Mounting instruction	DOC-0000711826
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00303654
3D-model	DOC-0000721425

Additional Information

This product can be customized alternatively in the following way: - Cable length from 300 to 5000 mm - Choice of RF connector (SMA, R-SMA, QMA, TNC, R-TNC, N) - Customer specific port labeling on pigtails - Further wireless bands, e.g. dual-band WiFi MIMO or Cellular/LTE SISO with GNSS

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.