

Indoor, MIMO, omni antenna, designed for ceiling mount installation

DESCRIPTION

- > Indoor, MIMO, omni antenna for the 698-960 MHz and 1710-6000 MHz
- > Designed for ceiling mount installation



ORDERING

Model	Product No.
Antenna with N-Type Connector	5005400
Antenna with 4.1/9.5 Mini-DIN Connector	5005400-mDIN
Antenna with 7/16-DIN Connector	5005400-DIN

SPECIFICATIONS

Electrical	
Frequency	Port 1 and 2: 698 - 960 MHz and 1710 - 6000 MHz
Max. Input Power	50 W
Polarisation	Vertical
3 dB Beamwidth, E-Plane	50 °
3 dB Beamwidth, H-Plane	360 °
Impedance	50 Ω
Gain	2dBd / 4.2dBi
Port-Port Isolation	> 10 dB
VSWR	< 1.5:1 and < 2.0:1
Passive Intermodulation	-150 dBc
In iBwave	Yes
Mechanical	
Connection(s)	2 / N-Type Female, 4.1/9.5 Mini-DIN Female or 7/16 DIN Female
Radome Material / Colour	LSZH UV stable ABS White
Dimensions	120 x 40 mm dian
Weight	1.5 kg / 3.31 lb
Mounting	Ceiling mount - dual point
Environmental	
Operating Temperature Range	-30°C to +70°C

ADDITIONAL DATA

