

Indoor, multi band, omni antenna, designed for ceiling
mount installation

DESCRIPTION

- > Indoor, multi band, omni antenna.
- > Designed for ceiling mount installation.
- > Available with N-Female, 4.1/9.5-Female, 4.3-10-Female or 7/16 DIN-Female connectors.



ORDERING

Model	Product No.
Antenna with N-Type Connector	5052450
Antenna with 4.1/9.5 Mini-DIN-Female Connector	5052450-mDIN
Antenna with 4.3-10-Female Connector	5052450-4310
Antenna with 7/16-DIN-Female Connector	5052450-DIN

SPECIFICATIONS

Electrical		
Frequency	695 - 960 MHz	1710 - 2700 MHz
Max. Input Power	50 W	
Polarisation	Vertical	
3 dB Beamwidth, H-Plane	360 °	
Impedance	50 Ω	
Gain	1dBd / 3.2dBi	
VSWR	< 1.8:1	< 1.5:1
Passive Intermodulation	< -153 dBc (2 x 43 dBm)	
In iBwave	Yes	
Mechanical		
Connection(s)	1 / N-Female, 4.1/9.5 Mini-DIN-Female, 4.3-10-Female or 7/16-DIN-Female on Plenum rated cable	
Radome Material / Colour	LSZH UV stable ABS White	
Dimensions	115 x 203mm dia	
Weight	0.4 kg / 0.88 lb	
Mounting	Ceiling Mount - single point	

ADDITIONAL DATA

