

## Flexible RF cable RG\_174\_A/U

### Description

RG: RG type RF cables

RG174, 50 Ohm, 1 GHz, 85°C, ø2.8 mm, PVC jacket



### Technical Data

#### Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper plated	Strand-07	0.48 mm
Dielectric	PE (Polyethylene)		1.48 mm
Outer conductor	Copper, Tin plated	Braid, 87%	2 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	2.8 mm +/- 0.12

Print: HUBER+SUHNER RG 174 A/U 50 Ohm (PA no.)

#### Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	1 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Screening effectiveness	≥ 40 dB (up to 1 GHz)
Operating voltage	≤ 1.5 kV <sub>rms</sub> (at sea level)
Test voltage	3 kV <sub>rms</sub> (50 Hz/1 min)

#### Mechanical Data

Weight		1.2 kg/100 m
Min. bending radius	static	15 mm
	repeated	28 mm
	dynamic	55 mm

#### Environmental Data

Temperature range	-25 °C ... +85 °C
Installation temperature	-20 °C... +60 °C
Halogen free	No
2011/65/EU (RoHS)	compliant
2006/1907/EC (REACH)	compliant

### Additional Information

#### Ordering Information

Order as RG\_174\_A/U

#### Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

#### Suitable Connectors

Cable group U2 2 mm / 50 Ohm

## Flexible RF cable RG\_174\_A/U

**Matrix** typical Attenuation [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] and maximum Power CW [ formula:  $(p/f^{0.5})$  ]

Coefficients:

a = 0.888

b = 0.034

f<sub>max</sub> = 1

P at 1GHz = 37

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,05	0,2	0,061	165
0,1	0,28	0,087	117
0,15	0,35	0,106	96
0,2	0,4	0,123	83
0,25	0,45	0,138	74
0,3	0,5	0,151	68
0,35	0,54	0,164	63
0,4	0,58	0,175	59
0,45	0,61	0,186	55
0,5	0,64	0,197	52
0,55	0,68	0,206	50
0,6	0,71	0,216	48
0,65	0,74	0,225	46
0,7	0,77	0,234	44
0,75	0,79	0,242	43
0,8	0,82	0,250	41
0,85	0,85	0,258	40
0,9	0,87	0,266	39
0,95	0,9	0,274	38
1,0	0,92	0,281	37