

Flexible RF cable SPUMA_400-FR

Description

Spuma: Flexible, low-loss RF cables (LMR* alternatives)

50 Ohm, 6 GHz, 85°C, ø10.25 mm, LSFH jacket, Flame retardant,
UL AWM style 1354



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Aluminium / Copper	Wire	2.74 mm
Dielectric	SPE (Foamed Polyethylene)		7.24 mm
Outer conductor	Aluminum / PES	longitudinal Foil, 100%	7.4 mm
Outer conductor	Copper, Tin plated	Braid, 78 %	8.15 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	10.25 mm +/- 0.1

Print: HUBER+SUHNER SPUMA 400-FR 50 Ohm (UL logo) AWM Style 1354 (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	78 pF/m
Velocity of signal propagation	85 %
Signal delay	3.9 ns/m
Screening effectiveness	≥ 90 dB (up to 6 GHz)
Operating voltage	≤ 1.6 kV _{rms} (at sea level)
Test voltage	3 kV _{rms} (50 Hz/1 min)
Voltage Rating UL	30 V

Mechanical Data

Weight		11.5 kg/100 m
Min. bending radius	static	25 mm
	repeated	100 mm

Environmental Data

Temperature range	-40 °C ... +85 °C
Temperature rating UL	60 °C
Installation temperature	-20 °C... +60 °C
Cold bend test	MIL-C-17 § 4.8.19
Flame propagation test	UL 1581 § 1100, UL 1581 § 1090, IEC 60332-3-24, EN 60332-1-2
Smoke density test	EN 61034-2
Halogen test	IEC 60754
Halogen free	Yes
2011/65/EU (RoHS)	compliant
2006/1907/EC (REACH)	compliant
2000/53/EC (ELV)	compliant
2012/19/EU (WEEE)	no special marking needed

Additional Information

*) LMR is a registered trademark of Times Microwave Inc.

Ordering Information

Order as SPUMA_400-FR

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group U30 7 mm / 50 Ohm

Flexible RF cable SPUMA_400-FR

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.1241

b = 0.008

f_{max} = 6

P at 1GHz = 600

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,3	0,07	0,021	1095
0,6	0,1	0,031	775
0,9	0,12	0,038	632
1,2	0,15	0,044	548
1,5	0,16	0,050	490
1,8	0,18	0,055	447
2,1	0,2	0,060	414
2,4	0,21	0,064	387
2,7	0,23	0,069	365
3,0	0,24	0,073	346
3,3	0,25	0,077	330
3,6	0,26	0,081	316
3,9	0,28	0,084	304
4,2	0,29	0,088	293
4,5	0,3	0,091	283
4,8	0,31	0,095	274
5,1	0,32	0,098	266
5,4	0,33	0,101	258
5,7	0,34	0,104	251
6,0	0,35	0,107	245