

Coaxial Cable Connector 11_BNC-50-7-16/122_U

Description

Straight cable plug

Interface standards
ABS2087.F02



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 4 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | crimped |
| Outer contact | crimped |
| Weight | 0.0431 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|--------------------------------|--|
| Centre contact | Copper Beryllium / Brass | Gold Plating (without Nickel underplating) |
| Outer contact | Brass | Nickel Plating |
| Body | Brass | Nickel Plating |
| Insulator | PTFE (Polytetrafluoroethylene) | |
| Coupling nut | Brass | Nickel Plating |
| Gasket | VMQ (Silicone rubber) | |
| Crimp ferrule | Brass | Nickel Plating |

Related Documents

| | |
|-----------------|--------------|
| Outline drawing | DOU-00102195 |
|-----------------|--------------|

Ordering Information

| | |
|----------------|-----------------------|
| Single package | 11_BNC-50-7-16/122_UE |
|----------------|-----------------------|

Additional Information

Remarks

Suitable cables: WD_EN4604--008, WN_EN4604-007