

Coaxial Cable Connector 11_QN-50-9-1/133_N

Description

Straight cable plug

Interface standards

QN QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	11 GHz		
Frequency range	DC to 2 GHz	2 to 4 GHz	4 to 6 GHz
Return loss	31.4 dB	30.4 dB	28 dB

Mechanical Data

Centre contact	plugged
Outer contact	crimped
Weight	0.0313 kg

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00340336
Assembly instruction	DOC-0000784192

Ordering Information

Bulk 100 pcs package	11_QN-50-9-1/133_NE
----------------------	---------------------

Additional Information

Suitable cables	SPUMA_500-FR-01
-----------------	-----------------