

Coaxial Cable Connector 16_QN-50-2-1/133_N

Description

Right angle cable plug

Interface standards

QN QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	11 GHz
Frequency range	DC to 1 GHz
Return loss	20 dB

Mechanical Data

Centre contact	soldered
Outer contact	crimped

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00080611
Assembly instruction	DOC-0000238606

Ordering Information

Single package	16_QN-50-2-1/133_NE
----------------	---------------------

Additional Information

Suitable cables	ENVIROFLEX_316_D, G_02232_D
-----------------	-----------------------------