

Coaxial Cable Connector 16_QN-50-4-1/133_N

Description

Right angle cable plug

Interface standards
QN QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω	
Interface frequency max.	11 GHz	
Frequency range	DC to 4 GHz	4 to 6 GHz
Return loss	24 dB	19 dB

Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0218 kg

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00007684
Catalogue drawing	DOU-00007046
Assembly instruction	DOC-0000178638

Ordering Information

Single package	16_QN-50-4-1/133_NE
Bulk 100 pcs package	16_QN-50-4-1/133_NH

Additional Information

Suitable cables	S_04262_D, LL142(Harbour)
-----------------	---------------------------